

*AMENDMENTS TO THE CLAIMS*

Please cancel, without prejudice, claims 53, 54, 73-83, 95 and 98 and amend claims 50, 55 and 94, as indicated below in the listing of claims.

**Listing of Claims:**

Claims 1-49 (Canceled).

50. (Currently Amended) A mounting foot for mounting a light bar to an exterior surface of a vehicle, the mounting foot comprising:

a base, the base having a light bar mounting surface for supporting the light bar;

a vehicle connector for connecting ~~the~~ said mounting foot to the vehicle, the vehicle connector secured to the base; and

a signaling device mounted to the base;

wherein the base includes a signaling device mounting surface and an underside, the signaling device being disposed on the signaling device mounting surface, the light bar mounting surface and the signaling device mounting surface being offset with respect to each other, and the underside having a vehicle mounting surface engageable with the vehicle, the vehicle mounting surface in opposing relationship to the light bar mounting surface, the signaling device mounting surface being disposed between the light bar mounting surface and the vehicle mounting surface.

51. (Previously Presented) The mounting foot according to claim 50 wherein the base has a first end and an opposing second end, the light bar mounting surface disposed adjacent the first end of the base, the signaling device disposed adjacent the second end of the base.

52. (Previously Presented) The mounting foot according to claim 50 wherein the base includes a contoured profile, the contoured profile configured to substantially conform to at least a portion of the exterior surface of the vehicle.

Claims 53 and 54 (Canceled).

55. (Currently Amended) The mounting foot according to claim ~~53~~ 50 wherein the base includes a sidewall, the sidewall and the signaling device mounting surface defining a recess, the signaling device disposed in the recess.

56. (Previously Presented) The mounting foot according to claim 55 wherein the signaling device includes at least one electrical wire extending therefrom, and the recess includes an opening through the base, the opening sized to allow the at least one electrical wire to extend therethrough.

57. (Previously Presented) The mounting foot according to claim 55 wherein the base includes an outer end, the outer end including a corner, the recess disposed at the corner of the outer end of the base.

58. (Previously Presented) The mounting foot according to claim 55, further comprising:  
a cover, the cover defining an interior, the signaling device disposed within the interior of the cover.

59. (Previously Presented) The mounting foot according to claim 58, wherein the cover is removably mounted to the base.

60. (Previously Presented) The mounting foot according to claim 58 wherein the cover comprises a transparent material.

61. (Previously Presented) The mounting foot according to claim 60 wherein the cover comprises a colored material.

62. (Previously Presented) The mounting foot according to claim 59, further comprising:

a seal member associated with the recess, the seal member cooperating with the cover to substantially seal the interior.

63. (Previously Presented) The mounting foot according to claim 62 wherein the base includes an underside, the underside having a vehicle mounting surface engageable with the vehicle, the mounting foot further comprising:

a second seal member, the second seal member being disposed in contacting relationship with the vehicle mounting surface of the base and in substantial alignment with the recess.

64. (Previously Presented) The mounting foot according to claim 50 wherein the base includes a mounting hole, the vehicle connector includes a roof clamp and a bolt, the roof clamp being substantially rigid and having a flange with an opening therethrough, the bolt extending through the opening of the roof clamp and into the mounting hole to secure the roof clamp to the base.

65. (Previously Presented) The mounting foot according to claim 50 wherein the signaling device comprises a light source.

66. (Previously Presented) The mounting foot according to claim 65 wherein the light source is pivotally mounted to the base.

67. (Previously Presented) The mounting foot according to claim 50 wherein the signaling device has at least one of a visual signaling feature and an aural signaling feature.

68. (Previously Presented) The mounting foot according to claim 50 further comprising:  
a second signaling device mounted to the base.

69. (Previously Presented) The mounting foot according to claim 67 wherein the base includes first and second signaling device mounting surfaces, the signaling device mounting surfaces each being in offset relationship to the light bar mounting surface, the first and second signaling devices being respectively mounted to the first and second signaling device mounting surfaces.

70. (Previously Presented) The mounting foot according to claim 69 wherein the base includes first and second sidewalls, the sidewalls respectively cooperating with the first and second signaling device mounting surfaces to define a first recess and a second recess, the first and second signaling devices disposed in the first and second recesses, respectively.

71. (Previously Presented) The mounting foot according to claim 70 wherein the base includes an outer end, the outer end including first and second corners, the first and second recesses respectively disposed at the first and second corners of the outer end of the base.

72. (Previously Presented) The mounting foot according to claim 70, further comprising:

first and second covers, the first and second covers each defining an interior, the first and second signaling device disposed in the interiors of the first and second covers, respectively.

Claims 73-83 (Canceled).

84. (Previously Presented) A vehicle comprising:  
an exterior surface; and  
a signaling system mounted to the exterior surface, the signaling system including:  
a light bar comprising a plurality of signaling devices supported on and distributed along a base member;  
a mounting foot having a generally planar light bar mounting surface supporting the base member of the light bar, the mounting foot secured to the exterior surface; and  
a signaling device mounted to the mounting foot.
85. (Previously Presented) The vehicle according to claim 84, wherein the base member of the light bar includes a pair of ends, the vehicle further comprising:  
a second mounting foot, the first and second mounting feet connected to the base member of the light bar such that the mounting feet are respectively disposed adjacent the first and second ends thereof, the second mounting foot connected to the exterior surface.
86. (Previously Presented) The vehicle according to claim 84 further comprising:  
a second signaling device mounted to the mounting foot.
87. (Previously Presented) The vehicle according to claim 86 wherein the mounting foot includes first and second sidewalls and first and second signaling device mounting surfaces, the first and second signaling device mounting surfaces each being offset with respect to the light bar mounting surface, the first and second sidewalls respectively cooperating with the first and second signaling device mounting surfaces to define a first recess and a second recess, the first and second signaling devices disposed in the first and second recesses, respectively.

88. (Previously Presented) The vehicle according to claim 87 wherein the mounting foot includes an outer end, the outer end including first and second corners, the first and second recesses respectively disposed at the first and second corners of the outer end thereof.

89. (Previously Presented) The vehicle according to claim 84 wherein the light bar includes an end, the mounting foot disposed at the end of the light bar, and the signaling device is mounted to the mounting foot such that the signaling device extends outwardly a predetermined distance from the end of the light bar.

90. (Previously Presented) The vehicle according to claim 84, wherein the light bar includes a pair of ends, the vehicle further comprising:

a second mounting foot, the second mounting foot connected to the light bar and to the exterior surface of the vehicle;

a second signaling device, the second signaling device connected to the second mounting foot;

wherein, the first and second mounting feet are connected to the light bar such that the mounting feet are respectively disposed adjacent the first and second ends thereof, and the first and second signaling devices are mounted to the first and second mounting feet, respectively, such that the signaling devices each extend outwardly a predetermined distance from the respective first and second ends of the light bar.

91. (Previously Presented) The vehicle according to claim 84 wherein the light bar comprises a single level light bar.

92. (Previously Presented) The vehicle according to claim 84 wherein the light bar comprises a multi-level light bar.

93. (Previously Presented) The vehicle according to claim 84 wherein the vehicle is an emergency vehicle.

94. (Currently Amended) An apparatus for mounting a light bar with a housing for light sources to a vehicle comprising:

a mounting foot joining the light bar to the vehicle;

at least one fastener for detachably securing the light bar to the mounting foot;

a mounting foot light source; and

a separate housing for the mounting foot light source supported on the mounting foot which is separate from the housing for the light sources of the light bar.

Claim 95 (Canceled).

96. (Previously Presented) The apparatus of claim 94 wherein the housing includes an opening for communicating power to the light source in the housing.

97. (Previously Presented) The apparatus of claim 94 wherein the housing includes a transparent cover that protects the light source while at the same time allows light from the light source to pass through it.

Claim 98 (Canceled).